



HITPOINT

SPECIFICATION

PRODUCT TYPE: PMOF-9745P-Q
(RoHS)

DSND BY		
CHKD BY		
APVD BY		

光 键 股 份 有 限 公 司

HITPOINT INC.



Add: No.4, Lane 505 ,Zhongzheng Road, Linkou Shiang, Taipei,Taiwan24445

Tel: + 886-2-2601-3311

FAX : + 886-2-2601-3898

<http://www.hitpoint.com.tw/>

1	Name: Omnidirectional Electret Condenser Microphone (Foil Electret Type)	
2	TYPE: PMOF-9745P-Q	
3	Electrical Specifications:	
3.1	Sensitivity Range	-34/36/38/40/42/44±3dB RL=2.2K Ω VCC=4.5V (1KHz 0dB=1V/Pa)
3.2	Impedance	Max .2.2K Ω 1KHz (RL=2.2K Ω)
3.3	Frequency	20-16000 Hz
3.4	Current Consumption	Max.0.5mA
3.5	Operation Voltage Range	1.0V-10V
3.6	Max. Sound Pressure Level	120dB S.P.L
3.7	S/N Ratio	More than 60dB
3.8	Sensitivity Reduction	4.5V-3.0V Sensitivity Variation less than 3dB
3.9	Typical Frequency Response Curve:	
	<p>A: Frequency Response, Magn dB re 1.000V/Pa</p>	
3.10	Schematic Diagram:	
4	Mechanical Specifications:	
4.1	Drawing	
4.2	Weight	0.66g

5. Reliability Tests: After any following tests, the sensitivity of the microphone unit shall not change more than $\pm 3\text{dB}$ from initial value, and shall keep their initial operation and appearance.				
	5.1	Hi-Temp. Test	To be no interference in operation after high temperature test $70\pm 3^{\circ}\text{C}$ for 48 hours The sensitivity to be within $\pm 3\text{dB}$ from initial sensitivity.	
	5.2	Low-Temp. Test	To be no interference in operation after Low temperature test $-20\pm 3^{\circ}\text{C}$ for 48 hours, the sensitivity to be within $\pm 3\text{dB}$ from initial sensitivity.	
	5.3	Isotherm& ISO-humidity Test	To be no interference in operation after storage test at temperature $40\pm 3^{\circ}\text{C}$ and relative humidity ($93\pm 3\%$) for 48 hours. The sensitivity to be within $\pm 3\text{dB}$ from initial sensitivity. the test is performed at temperature 20°C after operation for 6 hours.	
	5.4	Temperature Cycle Test	After exposure at $+55\pm 2^{\circ}\text{C}$ for 1 hour, at $20\pm 2^{\circ}\text{C}$ for 1 hour, at $-10\pm 2^{\circ}\text{C}$ for 1 hour, at $20\pm 2^{\circ}\text{C}$ for 1 hour, with 5 cycles. Change of sensitivity within $\pm 3\text{dB}$ from initial measuring should be done after 2 hours exposed to $20\pm 2^{\circ}\text{C}$.	
	5.5	Vibration Test	To be no interference in operation after vibration of full amplitude 2mm for 30 minutes at three axis, the sensitivity to be within $\pm 3\text{dB}$ from initial sensitivity.	
	5.6	Dropping Test	To be no interference in operation after dropped to concrete floor each time from 1- meter height of three directions in state of packing, the sensitivity to be within $\pm 3\text{dB}$ fro-initial sensitivity..	
6	Environmental Condition:			
	6.1	Storage condition	$-20^{\circ}\text{C}\sim +60^{\circ}\text{C}$ R.H. less than 45%~75%	
	6.2	Operation condition	$-10^{\circ}\text{C}\sim +45^{\circ}\text{C}$ R.H. less than 85%	
	6.3	Arbitration condition	Temperature : $20^{\circ}\text{C}\pm 1^{\circ}\text{C}$ Relative humidity: 63%~67% Air pressure : 86~106Kpa	
7	Notices:			
	7.1	All the soldering procedures upon microphones must be completed in a metallic device, the temperature of the soldering iron must be limited as $310^{\circ}\text{C}\pm 20^{\circ}\text{C}$.		
	7.2	Operators, the solder fixtures and the soldering irons must be statically grounded under each soldering process.		
8	Packing Specification			
	Drawing	Qty(pcs)	Size(mm)	Marking
	 Packing	100	98*98*15	QTY:100pcs
	 Middle Packing	600	205*105*50	QTY:600pcs